

KEY FEATURES

Real time 6D GNSS positioning system

- 3D position up to centimeter level
- 3D attitude information: Heading, Pitch and Roll

Smart and rugged design for easy integration and demanding environments

Ashtech Z-Blade Technology

- GNSS-centric engine
- GLONASS-only capable



ADU800 GNSS SENSOR

REAL TIME, INSTANTANEOUS 6D GNSS POSITIONING SYSTEM

Ashtech has raised the bar on GNSS attitude determination and real-time positioning with the ADU800, a 6D positioning system providing position + orientation for those who don't need to simply position a point, but want to position a platform!

The ADU800 is built on the strength of its predecessors, the Ashtech 3DF, ADU1, ADU2 and ADU5 and delivers unsurpassed accuracy in a rugged, full-function system. ADU800 provides precise heading, pitch and roll along with three-dimensional position up to centimeter-level of accuracy and velocities at a rate of up to 20 Hz for static and dynamic platforms, making it an ideal solution for a wide variety of airborne, marine and terrestrial applications.

ADVANCED FEATURES

The ADU800 from Ashtech is a three antenna GNSS system employing "on-the-fly" integer ambiguity resolution techniques using carrier phase measurements from the three on board GNSS receivers to provide instantaneous 3D attitude information. Attitude angular accuracies depend on the spatial separation between the three antennas and ADU800 can typically provide accuracies of 0.1 degree for heading and 0.2 degree for pitch and roll, using a 2 meter antenna separation.

The auto-calibration feature of the antenna setup, while supporting quite arbitrary installation geometry depending on platform limitations, remove the need of external calibration tools or complex / difficult installations.

In addition to the 3D attitude, the main GNSS board of the ADU800 is providing a 3D position up to centimeter-level accuracy in RTK mode when appropriate corrections feed the receiver.

The ADU800 can be readily used in GNSS applications such as gyrocompass calibration, open-pit mining, dredge positioning, seismic exploration and oceanographic research, airborne videography and remote sensing, as well as many other terrestrial, marine and airborne weapons and antenna pointing applications.

EASY INTEGRATION

The ADU800 is housed in a small, weatherproof, lightweight and rugged enclosure that is built around the GPS/GLONASS/SBAS MB100 and MB800 boards. Embedded Z-Blade™ technology ensures powerful performance and a patented way to use multiple GNSS constellations. It is fitted with a built-in power supply extending the input voltage range to between 9 and 36 V DC while maintaining a low power consumption regardless of the power input voltage.

The ADU800 can be operated in harsh environments while requiring a minimum of space for its installation. As a lightweight unit, the ADU800 is also compatible with airborne applications for which weight considerations are critical.

ASHTECH ADU800 GNSS SENSOR*

GNSS CHARACTERISTICS

- 210 (120+2*45) channels
 - GPS L1 C/A, L1/L2 P-code, L2C, L5
 - GLONASS L1 C/A, L2 C/A code
 - GALILEO E1 and E5
 - SBAS L1 (WAAS/EGNOS/MSAS/GAGAN)
 - QZSS
- Z-Blade technology (Ashtech GNSS centric algorithm) for optimal performance in harsh environment¹
- Quick signal detection engine for fast acquisition and re-acquisition of GNSS signals
- Fast and stable RTK solution + attitude solution
- Up to 20 Hz real-time raw data, position and heading output
- Advanced multi-path mitigation technique

REAL-TIME ACCURACY (HRMS)^{2,3}

SBAS (WAAS/EGNOS/MSAS)

- < 50 cm (1.64 ft)

DGPS

- 25 cm (0.82 ft) + 1 ppm⁴

RTK

- 1 cm (0.033 ft) + 1 ppm⁴

FLYING RTK

- 5 cm (0.165 ft) + 1 ppm⁴ for baselines up to 1000 km

VELOCITY ACCURACY² (knots)

- 95%: 0.1

REAL-TIME ATTITUDE ACCURACY⁵

1-METER ANTENNA SEPARATION

- Heading 0.2° rms
- Pitch/Roll 0.4° rms

3-METER ANTENNA SEPARATION

- Heading 0.06° rms
- Pitch/Roll 0.12° rms

10-METER ANTENNA SEPARATION

- Heading 0.02° rms
- Pitch/Roll 0.04° rms

REAL-TIME PERFORMANCE

INSTANT-RTK INITIALIZATION

- Typically 2-second initialization for baselines < 20 km
- Up to 99.9% reliability (user configurable)

RTK INITIALIZATION RANGE

- >40 km

TIME TO FIRST FIX²

- Re-acquisition 3 sec
- Hot start 15 sec
- Warm start 35 sec
- Cold start 45 sec
- < 1 minute cold start to first attitude data

RTK ROVER

- Up to 20 Hz Fast RTK
- RTCM-2.3 & RTCM-3.1
- CMR & CMR+
- DBEN, LRK & ATOM (Ashtech formats)
- Networks: VRS, FKP, MAC
- NMEA0183 messages output
- RTK with moving base operation
- Heading, pitch and roll determination with auto-calibration

I/O INTERFACE

- 3 RS232
- 1 USB 2.0 port
- 1 PPS output
- 1 Event marker input
- 3 TNC-F antenna connectors
- 5V power output on RS232 pin 9 (h/w jumper)

PHYSICAL CHARACTERISTICS

- Size (WxHxD): 190x58x160 mm (7.48x2.28x6.3 in) Width sliding bars included: 221.5 mm (8.72 in)
- Weight: 1.4 kg (3.08lb)

ENVIRONMENTAL CHARACTERISTICS

- Operating temperature: -30° to +60°C (-22° to +140°F)
- Storage temperature: -40° to +70°C (-40° to +158°F)
- Humidity: 100% condensing
- IP67
- Shock: MIL-STD 810F, Fig. 516.5-10 (40g, 11ms, saw-tooth)
- Vibration: MIL-STD 810F, Fig. 514.5C-175
- Speed (max): 514 m/sec (1,000 knots)
- Altitude (max): 18287 m (60,000 feet) RTK Initialization

POWER CHARACTERISTICS

- 9-36 VDC input
- Protected against over voltage up to 70 Volts and against reverse polarity
- Protected against electrical disturbances of vehicles with 12v and 24V supply voltages (ISO 7637 standard)
- Typical power consumption with 12 VDC input: 5.5W
- GNSS antenna(s) powered from 5 VDC (±10%); DC current: 100 mA max., 5 mA min

RECOMMENDED ANTENNAS

- Compact GNSS Machine/Marine/Aviation Antennas: Trimble AV33 & AV34
- GNSS Machine/Marine/Aviation Antennas: Trimble LV59 & AV59

CONFIGURATION TOOL

Ashtech Communicator is a GNSS utility for boards and sensors evaluation and configuration.

- Preset of commands
- Real-time data logging
- Real-time data visualization

ORDERING INFORMATION

- ADU800 is available in a variety of configurations

(*) Including all available options

- (1) All the available GNSS signals are processed equally and combined to improve performance in harsh environment.
- (2) Accuracy and TFF specifications may be affected by atmospheric conditions, signal multipath, satellite geometry and corrections availability and quality. Position accuracy specifications are for horizontal positioning. Vertical error is typically < 2 time's horizontal error.
- (3) Performance values assume minimum of five satellites, following the procedures recommended in the product manual. High multi-path areas, high PDOP values and periods of severe atmospheric conditions may degrade performance.
- (4) Steady state value after sufficient convergence time.
- (5) Typical values for properly installed antenna on vehicle body.



©2014 Trimble Navigation Limited. All rights reserved. The Ashtech logo, the Z-Blade logo and MB100 are trademarks of Trimble Navigation Limited. All other product and brand names are trademarks of their respective holders. 11/2014

AMERICAS
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
510 DeGuigne Drive
Sunnyvale, CA 94085 USA
+1-408-481-8000 Phone
Email: americasales-intech@trimble.com

EUROPE & MIDDLE EAST
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Germany
+49 (6142) 2100-348 Phone
France
+33 2 28 09 3800 Phone
Email: emeasales-intech@trimble.com

CHINA
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Email: chinasales-intech@trimble.com

ASIA - PACIFIC
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
Email: asiasales-intech@trimble.com

RUSSIA
TRIMBLE NAVIGATION LIMITED
Integrated Technologies
+49 (6142) 2100-348 Phone
Email: rusasales-intech@trimble.com